

TOP 5 CORRIDORS





Acknowledgements

Elected Officials

Darrell Steinberg Mayor

Jeff Harris (District 3) Vice Mayor

Angelique Ashby District 1

Allen Warren District 2

Steve Hansen District 4

Jay Schenirer District 5

Eric Guerra District 6

Rick Jennings, II District 7

Larry Carr District 8

City Staff

Ryan Moore Director of Public Works

David Edrosolan Interim Traffic Engineer

Jennifer Donlon Wyant Transportation Planning Manager

Leslie Mancebo, Project Manager Transportation Program Analyst

Project Mangement Team

Jesse Gothan Supervising Engineer

Megan Johnson Senior Engineer

William Shunk Senior Engineer

Phil Vulliet Senior Engineer

Ryan Billeci Senior Engineer

James Sellards Assistant Civil Engineer

Consultant Team

Fehr & Peers

David Carter

- Bob Grandy
- Adrian Engel

Emily Finkel

Becca Shafer

Cullen McCormick

Erika Kulpa

Mark Thomas

Aaron Silva

Josh Iniguez

AIM Consulting

Gladys Cornell

Nicole Porter



Table of Contents

Introduction

7

Countermeasure Toolbox

17





Vision Zero Top 5 Corridor





Appendix A-Related Documents Appendix B-Technical Calculations Appendix C-Concept Plans and Cost Estimates





TOP 5 CORRIDORS

1

1









Introduction

This report presents recommended roadway safety projects for the five one-mile roadway segments with the highest numbers of fatal and serious crashes involving pedestrians, bikes, and motor vehicles in the City of Sacramento. These corridors are:

- **Broadway/Stockton Boulevard:** Martin Luther King Jr. Boulevard to Stockton Boulevard and Broadway to 13th Avenue
- El Camino Avenue: Del Paso Boulevard to Steelhead Creek trail crossing
- **Florin Road:** 24th Street to Munson Way
- Marysville Boulevard: North Avenue to Arcade Boulevard
- Stockton Boulevard (South): McMahon Drive to Patterson Way

Each corridor has its own chapter documenting key features along the corridor such as neighborhood demographics, destinations, and travel statistics, as well as its crash analysis and proposed countermeasures, including their cost and effect on travel.



Top 5 Corridors



What is Vision Zero?

Vision Zero is a traffic safety philosophy that rejects the notion that traffic crashes are simply "accidents," but instead preventable incidents that can and must be systematically addressed. Vision Zero starts with the belief that everyone has the right to move safely in their communities, and that system designers and policy makers share the responsibility to ensure safe systems for travel. Through Vision Zero, the City of Sacramento and its partners are committed to working together to create safer streets. In January 2017, the City Council issued a call to action by adopting a resolution with the following goal: The City of Sacramento will work corroboratively in a data-driven effort to eliminate traffic fatalities and serious injuries by 2027. Thus, the Vision Zero Action Plan was created, and the document was approved by City Council August 2018.



What is the Vision Zero Top 5 Corridor Study?

This study represents a critical next step in the implementation of Sacramento's Vision Zero program, focusing efforts on implementing near-term roadway improvements on the five corridors within the City that have the highest rates of crashes that result in fatalities and severe injuries. These five corridors were identified through developing of the High Injury Network (HIN), which was developed as a part of the Vision Zero Action Plan. The HIN is based on seven years of crash data (2009 through 2015) for all travel modes, analyzed from the statewide Transportation Injury Mapping System (TIMS).



The "existing conditions" of these corridors (e.g., current travel trends and collision analysis for the years 2009 through 2017) were presented in the Vision Zero Top 5: Existing Conditions Report (see Appendix A).. The Top 5 Corridors Report contains the proposed countermeasures for each of the five corridors, including measured statistics on how implementation of the countermeasures will affect travel and how much they will cost.

Relationship to Vision Zero Action Plan

To help reach its goal of eliminating traffic fatalities and serious injuries by 2027, the City of Sacramento developed a Vision Zero Action Plan, which was adopted by the City Council in August 2018. The Plan used historic crash data to pinpoint the factors contributing to traffic deaths and serious injuries, and it identified proven safety countermeasures to address those factors through education, engineering, enforcement, and evaluation. This Top 5 Corridor Study represents a critical next step in the implementation of City of Sacramento's Vision Zero Program, focusing efforts on implementing near-term improvements on the five corridors within the City that have the highest rates of crashes that result in fatalities and severe injuries.

Identification of Segments

A High Injury Network (HIN) was developed for the City of Sacramento as part of the Vision Zero Action Plan. The HIN identifies corridors with the highest number of fatal and severe crashes for all travel modes (i.e., vehicle, bike, and pedestrian) to better understand existing transportation safety challenges in the City. Seven years of crash data, from 2009 through 2015, was analyzed from the statewide Transportation Injury Mapping Systems (TIMS). TIMS data includes only those crashes that resulted in an injury, ranging from "complaint of pain" to "fatal." Crashes resulting in only property damage, either to a vehicle or other property, are not included in the TIMS data set and were not analyzed as part of the Vision Zero Action Plan and HIN development.

A weighted crash score was created for each roadway segment; crashes involving a fatality or severe injury were given a score of 3, and all other injury crashes were given a score of 1. Weighted crash scores were then analyzed as a rate based on segment length. Segments with a weighted crash score greater than 1 per 300 ft of roadway were included on the HIN.

Once the HIN was developed, the network was divided into corridors approximately one mile in length, to allow for direct comparison and selection of the highest priority corridors. Fehr & Peers identified the ten corridors on the HIN with the highest number of fatal and severe injury crashes per mile.

Each of these corridors have between 10.4 and 7.1 fatal or severe injury crashes per mile. The next five ranked corridors (#6-10) have fatal and severe injury collision rates between 6.2 and 2.1.





Safety Context Overview

Total Crashes by Year

Figure 1 displays the number of annual injury crashes along each corridor between 2009 and 2017. This figure shows the following:

- The fewest crashes in a year occurred on the Broadway/Stockton Boulevard corridor in 2015, and the highest number of crashes in a year occurred on Florin Road in 2016.
- During the study period, Broadway/Stockton Boulevard is the corridor with the lowest number of total crashes, and Florin Road is the corridor with the highest number of crashes.
- While there were fewer overall crashes between 2012 and 2014, crashes are trending back up to peak numbers seen in 2009 and 2010.

Florin

Broadway/Stockton



Figure 1: Total Crashes by Year

Total Crashes by Mode

Figure 2 displays the number of injury crashes by mode along each corridor between 2009 and 2017 as total and percentages. This figure shows the following:

- Despite having the lowest number of crashes overall, the Broadway/Stockton Boulevard corridor has the largest share of crashes involving a bicyclist (24 crashes, or 20 percent).
- The Marysville Boulevard corridor has the largest share of crashes involving a pedestrian (25 crashes, or 13 percent).
- In absolute numbers, the Florin Road corridor accounts for the highest number of crashes involving pedestrians (28 crashes), bicyclists (29 crashes), and vehicle-vehicle crashes (192 crashes).

Pedestrian



*One crash on El Camino involved both a pedestrian and a bicyclist.

Figure 2: Total Crashes by Mode

Total Crashes by Severity

Figure 3 displays the number of crashes that resulted in a fatality or serious injury (also called a KSI) along each corridor between 2009 and 2017. This figure shows the following:

• Despite having the lowest number of total crashes overall, the Broadway/Stockton Boulevard corridor has the largest share of

Figure 3: Total Crashes by Severity

crashes that result in a fatality or serious injury (15 crashes, or 12 percent of all injury crashes).

- The Marysville Boulevard corridor has the highest absolute number of crashes resulting in a fatality or serious injury (19 crashes).
- Throughout this report, the acronym KSI is used to denote crashes where someone was killed or seriously injured.



.

KSI Crashes by Mode

Figure 4 displays the number of crashes by mode that resulted in a fatality or serious injury between 2009 and 2017. This figure shows the following:

- The Marysville Boulevard corridor has the highest number and largest share of KSI crashes that involved a pedestrian (11 crashes, or 58 percent of KSI crashes).
- The Stockton Boulevard (South) corridor has the highest number and largest share of KSI crashes that involved a bicyclist (four crashes, or 25 percent of KSI crashes).
 The El Camino Avenue corridor does not have
- The El Camino Avenue corridor does not have any bike crashes that resulted in a fatality or serious injury.

Bike KSI



Figure 4: KSI Crashes by Mode



TOP 5 CORRIDORS



ú)

at the

and the second second

TE

CADE



Countermeasure Toolbox

Introduction

This toolbox presents the roadway safety countermeasures applicable on each of the Top 5 Corridors. These countermeasures have been selected specifically for their efficacy in creating safer environments for people traveling on Sacramento's streets, regardless of mode. Many of the countermeasures are included in the Caltrans Local Roadway Safety Manual (LRSM) and can be advantageous for use in Caltrans Highway Safety Improvement Program (HSIP) grant funding applications. In the toolbox, these countermeasures are noted by an LRSM ID numbers, and include a Caltrans-approved Crash Reduction Factor (CRF) as defined in the LRSM. The higher the CRF, the greater the expected reduction in crashes. There are many effective safety countermeasures beyond those listed in the LRSM, and several are included in this toolbox. Some of these countermeasures include an associated CRF, which is based on academic research and before-and-after studies, as compiled and reported by the Federal Highway Administration (FHWA).

How to use the Toolbox

A-Z

The countermeasure tools are listed in alphabetical order.



Description (

List of Countermeasures





Advanced Dilemma- Advanced Stop Bar Zone Detection





Bike Conflict Zone Markings



Bulbout



Class II Bike Lane



Close Sidewalk Gap Co-Locate Bus Stops & Pedestrian Crossings



Extend Bike Lane to Intersection



Extend Pedestrian Crossing Time



Leading Pedestrian



Parking Prohibition



Pedestrian Scramble



Bus Boarding Islands



Consolidate Driveways



Extend Signal Clearance Time



Median Barrier Fencing



Partial Closure



Prohibit Left Turn



Signal Heads

High Visibility

Crosswalk

Narrow Lanes

Countdown Pedestrian Dual Curb Ramps

Intersection

Tightening

New Pedestrian

Signal











Interval



New Traffic Signal



Pedestrian Scale Lighting



Island

Pedestrian Recall

Signal Timing











List of Countermeasures (cont.)



Realign Intersection

to 90 Degrees

Remove Sight

Obstruction







Prohibit Turns During Protected Left Turns Provide Green Time Raised Intersection Pedestrian Phase





Remove Dual Left Turn Lanes



Roundabout







Shorten Signal Cycle Length

Widen Sidewalk

Slow Green Wave

Road Closure

Split Signal Phase

Stop Sign

Separated/Buffered Bikeway

Raised Median

Remove Right Turn

Slip Lane







Red Light Camera	Re



Countermeasures A-C



Advanced Dilemma-Zone Detection

Signals/Signage

Advanced dilemma-zone detection enhances safety at signalized intersections by modifying traffic control signal timing on the fly to reduce the number of drivers that may have difficulty deciding whether to stop or proceed during a yellow phase. This may reduce rear-end crashes associated with unsafe stopping and angle crashes due to red light running.



Bike Conflict Zone Markings

Bike Safety

Green pavement within a bike lane to increase visibility of bicyclists and to reinforce bike priority. The green pavement is used as a spot treatment in conflict areas such as driveways.



Advanced Stop Bar

Crossing, Pedestrian Safety

A stop bar placed ahead of the crosswalk at stop signs and signals reduces instances of vehicles encroaching on the crosswalk.



Bulbout

🗷 Crossings, Pedestrian Safety, Speed, Visibility

Raised devices, usually constructed from concrete, landscaping, or paint and plastic materials, that narrow the roadway to reduce speeds of turning vehicles, improve sight lines, and shorten pedestrian crossing distances.



Bus Boarding Islands

Bike Safety, Pedestrian Safety

Dedicated waiting and boarding areas for passengers that are separated from the sidewalk by a bike channel, eliminating conflicts between transit vehicles and bikes at stops.



Class II Bike Lane

Bike Safety

Five to seven foot wide designated lanes for bicyclists adjacent to vehicle travel lanes, delineated with pavement markings.

Countermeasures C - D



Close Bike Lane Gap

Bike Safety

Closing gaps between bike lanes increases the amount of dedicated facilities bicyclists can use, reducing mixing of bicyclists and drivers and increasing network connectivity and visibility of bicyclists in the roadway.



Close Sidewalk Gap

Pedestrian Safety

Providing continuous sidewalks for pedestrians provides a separated facility for people to walk along the roadway, and can help minimize crashes with pedestrians walking in the road.



Co-Locate Bus Stops and Pedestrian Crossings

Crossing, Pedestrian Safety

Place bus stops and pedestrian crossings in close proximity to allow transit riders to cross the street safely.



Consolidate Driveways

Bike Safety, Pedestrian Safety, Visibility

Reducing the number of driveway entrances/ exits through consolidation limits the exposure of bicyclists, pedestrians, and drivers to vehicles entering or exiting driveways, reducing conflicts.



Countdown Pedestrian Signal Heads

Crossings, Pedestrian Safety, Signals/Signage

Displays "countdown" of seconds remaining on the pedestrian signal. Countdown indications improve safety for all road users, and are required for all newly installed traffic signals where pedestrian signals are installed.



Dual Curb Ramps

Pedestrian Safety

Dual curb ramps, opposed to single angled curb ramps, improve ADA accessibility at all intersection approaches so that pedestrians with mobility challenges, or those pushing carts or strollers, can safely enter and exit all crosswalks. These are curb ramps that provide a slope for two directions of the curb, instead of single angled curb ramps.

Countermeasures E - L



Extend Bike Lane to Intersection

Bike Safety

In locations where a bike lane is dropped due to the addition of a right turn pocket, the intersection approach may be restriped to allow for bicyclists to move to the left side of right-turning vehicles ahead of reaching the intersection.



Extend Pedestrian Crossing Time

Crossings, Pedestrian Safety

Increases time for pedestrian walk phases, and can better accommodate vulnerable populations such as children and the elderly.



Extend Signal Clearance Time

Signals/Signage

Extending yellow and all red time allows drivers and bicyclists to safely cross through a signalized intersection before conflicting traffic movements are permitted to enter the intersection.



High Visibility Crosswalk

Crossings, Pedestrian Safety, Visibility

A crosswalk designed to be more visible to approaching drivers, striped with ladder markings using high-visibility material such as thermoplastic tape instead of paint.



Intersection Tightening

Crossings, Pedestrian Safety, Speed, Visibility

Uses temporary materials like paint, plastic bollards, and reflective markers to visually and physically narrow the street at intersections, which can create a shorter crossing for pedestrians and slows vehicles approaching the intersection and turning.



Landscape Buffer

Pedestrian Safety

Separating drivers from bicyclists and pedestrians using landscaping provides more space between the modes and can produce a traffic calming effect by encouraging drivers to drive at slower speeds, lowering the risk of crashing.

Countermeasures L - P



Leading Pedestrian Interval

Crossings, Pedestrian Safety, Visibility

Traffic signals timed to allow pedestrians a short head start in crossing an intersection to minimize conflicts with turning vehicles and improve pedestrian visibility.



Median Barrier Fencing

🗇 Crossings, Pedestrian Safety

Pedestrian median barriers restrict pedestrians from crossing the median at locations where nearby crossings are available and midblock crossings may have poor sight lines or insufficient safety enhancements for the conditions.



Narrow Lanes

Speed

A reduction in lane width, to 11 feet, produces a traffic calming effect by encouraging drivers to travel at slower speeds, lowering the risk of crashing with bicyclists, pedestrians, and other drivers.



New Pedestrian Signal

Crossings, Pedestrian Safety

Pedestrian signals (also called "half signals") can be implemented at mid-block crossing locations to enhance crosswalk safety and increase driver yielding. The signals consist of standard (redyellow-green) signal heads controlling the roadway approaches, and function similar to a standard traffic signal when actuated by a pedestrian or bike pushbutton or detection.



New Traffic Signal

Signals/Signage

New traffic signals help organize travel of all modes at an intersection, limiting interactions between vehicles, pedestrians, and bicyclists with conflicting movements. New signals can have a traffic calming effect on long, high-speed straightaways.



Parking Prohibition Near Intersections

Ø Bike Safety, Crossings, Pedestrian Safety, Signals/Signage

By restricting parking at curbs in front of intersection crosswalks, sight lines are cleared between pedestrian crossings and oncoming drivers, reducing the risk of crashing (also called "daylighting).

Countermeasures P - P



Partial Closure Bike Safety, Crossings, Pedestrian Safety

Partial closures, using a physical barrier across one direction of traffic at an intersection allow full bicyclist and pedestrian passage while restricting vehicle access in one direction. This strategy can be used to minimize conflict points at complicated intersections.



Pedestrian Recall Signal Timing

Pedestrian Safety, Signals/Signage

Signals can be put in "recall" for key time periods of the day such as peak business hours or school drop-off/pick-up times. The "WALK" signal would be displayed every signal cycle without prompting by a pedestrian push button.



Pedestrian Refuge Island

Crossings, Pedestrian Safety, Speed, Visibility

Pedestrian refuge islands provide a protected area for pedestrians at the center of the roadway. They reduce the exposure time for pedestrians crossing the intersection and simplify crossings by allowing pedestrians to focus on one direction of traffic at a time.



Pedestrian Scale Lighting

Crossings, Pedestrian Safety, Visibility

Appropriate quality and placement of lighting can enhance an environment as well as increase comfort and safety. Pedestrian-scale lighting is lower in height than standard streetlighting and is spaced closer together.



Pedestrian Scramble

Crossings, Pedestrian Safety, Signals/Signage

Restricts vehicular movements to provide an exclusive signal phase allowing pedestrians to cross in all directions, including diagonally.



Prohibit Left Turn

Bike Safety, Crossings, Pedstrian Safety, Signals/Signage

Prohibitions of left turns at locations where a turning vehicle may conflict with pedestrians in the crosswalk or where opposing traffic volume is high. Reduces pedestrian interaction with vehicles when crossing.

Countermeasures P - R



Prohibit Turns During Pedestrian Phase

Crossings, Pedestrian Safety, Signals/Signage

Restricts left or right turns during the pedestrian crossing phase at locations where a turning vehicle may conflict with pedestrians in the crosswalk. This restriction may be displayed with a blank-out sign.



Protected Left Turns

Signals/Signage

Protected left turns provide an exclusive phase for left-turning vehicles to enter an intersection separate from any conflicting vehicle or pedestrian movements.



Provide Green Time For Bikes

Bike Safety, Signals/Signage

Provide or prolong the green phase when bicyclists are present to provide additional time for bicyclist to clear the intersection. Can occur automatically in the signal phasing or when prompted with bike detection. Topography should be considered in clearance time.



Raised Intersection

Crossings, Pedestrian Safety, Speed

Raised intersections are flush with the sidewalk and ensure that drivers traverse the crosswalk slowly. Similar to speed humps and other vertical speed control elements, they reinforce slow speeds and encourage motorists to yield to pedestrians at the crosswalk.



Raised Median

Crossings, Pedestrian Safety, Speed

Curbed sections in the center of the roadway that are physically separated from vehicular traffic. Raised medians can also help control access to and from side streets and driveways, reducing conflict points.



Realign Intersection to 90 Degrees

Crossings, Pedestrian Safety, Speed, Visibility

By eliminating acute or obtuse angles between intersection roadways, intersection sight distance may be improved, allowing drivers to see pedestrians more easily. Right-angle intersections can also help to slow down turning vehicles.

Countermeasures R - R



Red Light Camera

Signals/Signage

Red light cameras can be used for automated enforcement to issue citations to drivers running red lights at signalized intersections, and may discourage this behavior.



Relocate Crosswalk

Crossings, Pedestrian Safety, Visibility

Relocating existing crosswalks can help improve pedestrian visibility, shorten crossing distances, and minimize conflicts with vehicles. In some cases, crosswalks currently located between two legs of an offset intersection may be moved to the far side of the intersection to minimize the number of conflicting vehicle turning movements.



Remove Dual Left Turn Lanes

Signals/Signage

Restriping an approach so there is a single leftturn lane instead of dual lefts can help simplify an intersection and create room for a road diet or other geometric improvements.



Remove Right Turn Slip Lane

Bike Safety, Pedestrian Safety, Speed

Closing a free-flow right-turn slip lane can help slow right turning drivers, eliminates an uncontrolled crossing for pedestrians, and shortens pedestrian crossing distances. The space reclaimed in closing the slip lane can be reused as pedestrian space to widen sidewalks, enhance curb ramps, or provide more space for street furniture.



Remove Sight Obstruction

Visibility

Remove objects that may prevent drivers and pedestrians from having a clear sightline. May include trimming or removing landscaping, or removing or relocating large signs.



Road Closure

Bike Safety, Crossings, Pedestrian Safety

Road closures, using a physical barrier, allow full bicyclist and pedestrian passage while restricting vehicle access. This strategy can be used to minimize conflict points at complicated intersections or to minimize conflicting movements due to turning vehicles.

Countermeasures R - S



Road Diet

Speed, Pedestrian Safety, Bike Safety, Crossings

Road diets generally reassign space in the roadway from vehicle travel lanes to create room for bike facilities, wider sidewalks, or center turn lanes. Road diets optimize street space to benefit all users by improving the safety and comfort of pedestrians and bicyclists, and reducing vehicle speeds and the potential for rear end crashes.



Separated/Buffered Bikeway

Bike Safety

Designated bike lanes, separated from vehicle traffic by a physical barrier, usually bollards, landscaping, or parked cars. These facilities can increase safety by decreasing opportunities for crashing with overtaking vehicles, and reducing the risk of dooring.



Roundabout

Ø Bike Safety, Crossings, Pedstrian Safety, Signals/Signage

Roundabouts are large circular islands, placed in the middle of an intersection, which direct flow in a continuous circular direction around the intersection. Roundabouts can reduce the number of conflict points, compared to an uncontrolled intersection, and decrease vehicle speeds due to intersection geometry. Converting signalized intersections to roundabouts can be especially effective at complex intersections or intersections with high left-turn volumes.



Shorten Signal Cycle Length

Signals/Signage

Reducing the cycle length at intersections may reduce the delay experienced by vehicles, bicyclists, and pedestrians. When delay is significant, road users are more inclined to ignore signal indications.



Slow Green Wave

Signals/Signage, Speed

A series of traffic signals coordinated to allow for slower vehicle travel speeds through several intersections along a corridor. Coordinating signals for slower travel speeds gives bicyclists and pedestrians more time to cross safely and encourages drivers to travel at slower speeds.



Split Signal Phase

Signals/Signage

Opposing legs of an intersection each receive their own phase.

Countermeasures S - W



✓ Signals/Signage

When warranted, stop signs provide a cue to drivers to stop and wait for vehicles, bicyclists, and pedestrians to cross before proceeding.



Straighten Crosswalk

🕫 Crossings, Pedestrian Safety, Visibility

Straightening crosswalks improves sight lines, making pedestrians more visible to oncoming drivers, and may shorten the crossing distance, reducing the length of time required for pedestrians to cross an intersection.



Widen Sidewalk

Pedestrian Safety

Wide sidewalks can provide space for both pedestrians and bicyclists to use a shared facility. Wide sidewalks can be important for locations with high volumes of pedestrians.



TOP 5 CORRIDORS



- State



Policy Toolbox

Introduction

As part of the Vision Zero Action Plan, adopted by City Council in August 2018, the City committed to a series of actions that focus on achieving the Vision Zero goal of eliminating traffic fatalities and serious injuries. The development of the Top 5 Corridor Study has provided additional insight into specific tools to consider when updating policies to achieve the Vision Zero goal. Clearly defining policies will allow them to be regularly incorporated into future plans and projects.

Signal Policies

Consistent with Vision Zero Action 5.4 it is recommended that the City update its signal timing policy to improve safety for all modes.

Based upon experience on the Top 5 corridors, some signal timing policies to consider as part of this update include the following:



Recommend that the City consider establishing a practice to determine a maximum cycle length for a corridor or intersection, especially along the High Injury Network.

What is Maximum Cycle Length?

A cycle length is the amount of time required to display all phases (red, yellow, green) for each direction of an intersection before returning to the starting point. Cycle lengths are based on traffic volumes and work best within a certain range depending on the conditions of the corridor and intersection. Shorter signal cycles can reduce overall pedestrian wait times and result in improved pedestrian compliance.



Recommend that the City review industry best practices, State and Federal guidance to update the practice for calculating minimum green time with the next update to City signal timing policy.

What is Minimum Green Time?

The minimum green time is the least amount of time that a green signal will be displayed for a specific movement. The time for pedestrians and/or bicyclists crossing with a phase must also be considered and included in the minimum phase length.



Recommend that the City review its practice for calculating pedestrian clearance time with the next update to City signal timing policy.

What is Walk/Flash Don't Walk Time?

The "Flashing Don't Walk" interval follows the "Walk" interval and is often accompanied by a countdown signal. It is used to alert pedestrians that they need to finish crossing and if there is a countdown, it lets pedestrians know how long they have to do so.



Recommend that the City review its practice for calculating intersection clearance times with the next update to City signal timing policy.

What are Clearance Times?

Clearance times include the yellow light and the "all-red" signal time. The yellow signal provides time for approaching vehicles to slow and stop and the "all-red" is the time when a signal is changing from one phase (red, yellow, green) to the next giving time for all vehicles to clear the intersection.



Recommend that the City investigate controlling the travel speed of vehicles by optimizing the cycle length, splits, and offsets to the posted speed or lower where appropriate.

What is a Slow Green Wave?

The concept of a "slow green wave" is a series of traffic signals coordinated to allow for uninterrupted traffic flow of vehicles traveling at the speed limit or lower and require those traveling at faster speeds to stop more frequently.



Recommend that the City consider implementing pedestrian recall mode to traffic signals on the High Injury Network where appropriate.

What is Pedestrian Recall and Detection?

Activating pedestrian recall mode initiates the pedestrian phase automatically with its corresponding phase for every traffic signal cycle. This means that the pedestrian would not have to push a button in order to see the "Walk" phase. This is typically implemented in areas with high levels of pedestrian activity.

Street Design Policies

Consistent with Vision Zero Action 2.1 it is recommended that the city update street design standards to reflect complete streets and designs reflective of crash reduction factors.

Based upon experience on the Top 5 corridors, some tools to consider as part of this update include the following:



Recommend that the City continue its efforts to install pedestrian countdown signals at all signalized intersections.

What are pedestrian countdown signals?

Per the City's draft Pedestrian Crossing Guidelines, pedestrian countdown signals are particularly useful to pedestrians at longer distance crossings, so pedestrians know how much time remains to fully cross the street before the signal changes.



Recommend that the City install the appropriate bike facility based on the guidance in the Sacramento Bicycle Master Plan.

How are bikeways selected?

The Sacramento Bike Master Plan contains a "Bikeway Facility Selection Guidelines" chart to provide a starting point to help identify which bikeway type is appropriate for a road based on its traffic volume and speed limit. Using this chart to build appropriate bike facilities will create a low stress network that is comfortable for riders of all ages and abilities to use.



Recommend that the City consider a contextual approach to setting the minimum widths of sidewalks with the next update to the street design standards.

How are sidewalk widths determined?

In accordance with ADA accessibility guidelines, sidewalks should at least 5 feet in width. A contextual approach for sidewalk width setting could take into consideration the street type and surrounding land use, requiring wider sidewalks on some streets to enhance safety and comfort for pedestrians.



Recommend that the City consider exemptions to the standard minimum lane width on the Top 5 Corridors and remaining High-Injury Network, where appropriate.

How are lane widths determined?

City street design standards require minimum lane widths for specific scenarios. A reduction in lane width produces a traffic calming effect by encouraging drives to travel at slower speeds. Other considerations for setting minimum lane widths are truck routes, transit routes, and locations where adjacent lanes are in the opposite direction.

Other Policies

This section documents additional recommended policy modifications based upon experience on the Top 5 corridors:



Recommend that the City continue to pursue efforts to reduce posted speed limits on the HIN.

How are speed limits set?

State guidelines require surveys of current speeds to be used as the basis for speed limit setting. While continuing to operate within State guidance the City has some tools to ensure that speed limits on the HIN are context sensitive and prioritize the safety and comfort of all road users.



Recommend that the City support the use of automated speed enforcement in State Legislation.

What are speed safety cameras?

Speed safety cameras are devices that can identify speeding violations and issue citations. This type of speed enforcement is allowed in many States, it is not allowed in California. The City of Sacramento should continue to support legislative efforts to allow speed safety cameras in California.



Bus Stop Placement and Supportive Facilities Recommend that the City prioritize pedestrian and bike safety improvements that provide connections to light rail stations and bus stops. At minimum, bus stops should be co-located with an adjacent crosswalk (within 100 feet).

How are bus stop placements determined?

Consistent with the City's draft Pedestrian Crossing Guidelines, recommend that bus stops are placed on the far side of intersections and downstream of adjacent crosswalks, to ensure bus stop does not conflict with crosswalk approach. Recommend that the City also provide adequate sidewalk width on streets with bus routes to provide stop amenities while maintaining space for pedestrian flow.

Newly Adopted or In Process Policies



In December 2019, the City adopted a Complete Streets Policy to promote safe and convenient travel options on Sacramento's streets for all users of all abilities and ages.

This policy aligns with and supports projects and policies recommended as part of this report, as well as the Action Items listed in the Sacramento Vision Zero Action Plan.



Recommend that the City update the Pedestrian Crossing Guidelines later this year. The updated guidelines, currently in draft form, will include recommendations related to crosswalk spacing, markings, and safety enhancement facilities.

Key considerations included in the draft Guidelines support the crosswalk safety enhancement recommended in this report. Additionally, marked crosswalk spacing is recommended at least as frequently as shown below:

- Every 800 feet on the Grid
- Every 1,200 feet on the HIN
- Within 100 feet of new transit stops


TOP 5 CORRIDORS





ł



TOP 5 CORRIDORS



I Camino Avenue at Del Paso Boulevard

 \ominus



Ounino Π

Vision Zero Top 5 Corridor

El Camino Avenue

Vision Zero Top 5 Corridor



El Camino Ave & Del Paso Blvd

What is going on?

Between 2009 and 2017, 11 crashes that resulted in a fatality or severe injury (KSI) occurred on the segment of El Camino Avenue between Ueda Parkway and Del Paso Boulevard, three of which involved a pedestrian.

What are the key issues?

Many of the vehicular crashes involved rear-ends, proceeding straight, and driving at an unsafe speed. Additionally, two-thirds of pedestrian crashes involved people crossing the street in a marked crosswalk.

What is the community concerned about?

During outreach, residents spoke of drivers traveling too fast on the corridor, which can make it difficult to cross the street or pull out of driveways.

The following pages lay out the existing conditions along the corridor, feedback heard from residents at outreach events, and roadway safety recommendations focused on reducing vehicle speed, improving visibility, increasing compliance with signals and signs, and providing additional crossing opportunities for pedestrians.

Table of Contents

A-4

In the Neighborhood Travel on **El Camino**

A-6

A-8 A-10 **A-11**

Safety on **El Camino** Feedback from the Community **Investments to Enhance Safety**



Conceptual Design for El Camino



How Will Travel Change?



How Much Will the Project Cost?

In the Neighborhood

Corridor



About the Neighborhood









Key Destinations Along the Corridor

Parks



Food Markets



Regional Trails



Houses of Worship



Libraries



Travel on El Camino

Key Statistics





Crashes on El Camino

Vehicle Crash Types



Crash Locations



Pedestrian Crash Types



Numbers that are turned on represent a location where crash type has occurred at least three times.



Bike Crash Types

*One crash involved both a pedestrian and bicyclist and is identified under both mode categories



Feedback from the Community

"

At the intersection of Del Paso and El Camino, it is hard to cross the street."

"

A lot of homes have their driveways backing into El Camino—there is unsafe backing out due to high speeds and visibility issues."

Key Themes

Visibility

Residents provided feedback related to nighttime visibility issues due to insufficient lighting, and difficulty turning onto El Camino from driveways and side streets due to sight line issues.

Speed

Residents described drivers traveling at speeds they felt were too fast, which makes driving and walking along and crossing El Camino feel uncomfortable for them.



Signals/Signage

Residents described drivers often running red lights and pedestrians crossing against the light - both behaviors theorized to be because of long traffic signal cycle lengths.

Bike Safety

Residents provided feedback that the existing bike lanes are too narrow and often obstructed, and that fastmoving vehicle traffic makes biking uncomfortable.

Crossings

Residents described difficulty in crossing the street at the El Camino/Del Paso intersection due to long distances, long waits, and a missing marked crosswalk.



Engagement Events

November 10, 2018

Old North Sacramento / Dixieanne Community Association Meeting December 4, 2018 Grocery Outlet Store Pop-Up Event

June 6, 2019

Greater Sacramento Urban League Open House Event

Investments to Enhance Safety

Key Crash Countermeasures











Location-Specific Recommendations



Note: Maintain existing 10 foot travel lanes on El Camino Avenue





Location-Specific Recommendations







Location-Specific Recommendations









Location-Specific Recommendations



Project Options

Option 1: Close south leg of Traction Ave, north leg of Traction Ave, south leg of Altos Ave, and Hawhtorne Ave is right-in/right-out only. Square up north leg of Altos Ave and install a traffic signal.

Option 2: Close north leg of Traction and south leg of Altos Ave. Hawthorne Ave is right-in/rightout. Square up north leg of Altos Ave and south leg of Traction Ave. Install raised intersection and traffic signal with pedestrian scramble to serve bike and pedestrian traffic using Sacramento North Bike Trail. This option is shown in the concept plans.





Location-Specific Recommendations







Location-Specific Recommendations







* The Del Paso Boulevard Road Diet is not a part of the Top 5 Corridors Plan





Location-Specific Recommendations



El Camino Avenue/Del Paso Boulevard/Beaumont Street Queues

El Camino Avenue is a two-lane, 30-miles-per-hour roadway for most of the study corridor, but east of Del Paso Boulevard, it widens to four-lanes and the posted speed limit increases to 35-miles per hour. It provides an east-west connection over Steelhead Creek and to I-80 Business Loop. As a result, the El Camino Avenue/Del Paso Boulevard/Beaumont Street intersection is very busy. Conditions may be exacerbated with the Vision Zero recommended road diet on Del Paso Boulevard. According to the City's General Plan, the intersection is exempt from the City's LOS D standard and can operate at LOS E conditions during peak hours acceptably.

How Will Travel Change?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 2 and 5 mph as a result of the proposed project. While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes. Additionally, the new traffic signals will create gaps in traffic that will improve access from side-streets and driveways.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to increase between 31 and 84 seconds as a result of the proposed project.

Estimated Changes with Project



Without project With project 97% (12,150 ft) 100% (12,500 ft) Bike Lane Coverage





Number of Locations Upgraded to Controlled Crossings



Number of Marked Crosswalks



How Much Will the Project Cost?

El Camino Avenue Cost Summary

\$16,450,000

Construction

Construction costs include the cost to build the primary items associated with the safety countermeasures for the corridor. The items were estimated based on the preliminary design concepts and recent construction bid unit costs with an escalation factor to account for future construction. The costs were broken down into two categories that consisted of major roadway items and electrical items such as traffic signals and lighting. A contingency factor was included to account for refinement of project design, changes in project details, or unforeseen changes in construction costs.

Actual project costs will be determined by surveyed base mapping, geotechnical reports, concept refinement, environmental reviews, right of way availability, project phasing, and bid conditions at the time of advertisement. Project costs should be reviewed prior to any grant application or initiation of a Capital Improvement Project to revalidate and update the assumptions in this study as necessary.



The total project costs shown in the summary chart have been escalated at an assumed 3% per year escalation factor to 2025, the anticipated year of construction.

Right of Way

In addition to construction costs, right of way costs were assumed that include temporary construction easements for items such driveway modifications, curb ramps reconstruction, signal equipment poles and cabinets. It was assumed that each project could be constructed almost exclusively within the roadway prism and right of way acquisition would not be needed along the entire project frontage. Further refinement of the base mapping in subsequent phases of design will more accurately identify specific right of way needs.

Delivery

Project delivery costs are included in the estimates provided in this study. These costs encompass all of the work to complete subsequent phases including preliminary engineering, environmental documentation, final design, right of way engineering, and construction oversight. A breakdown of these costs is provided in Appendix C.



B NS NB

Vision Zero Top 5 Corridor

Marysville Boulevard

Vision Zero Top 5 Corridor



Marysville Blvd - Greater Sacramento Urban League/Vic Fazio Training Center

What is going on?

Between 2009 and 2017, 19 crashes that resulted in a fatality or severe injury (KSI) occurred on Marysville Boulevard between North Avenue and Arcade Boulevard. Three of these crashes involved a bicyclist and 11 of the crashes involved a pedestrian.

What are the key issues?

Two-thirds of drivers were proceeding straight or stopped at the time of the crash, and alcohol was involved in over half the crashes that resulted in a KSI. Additionally, two thirds of pedestrian crashes involved a person crossing the street in a marked crosswalk, and three-fourths of bike crashes were broadside, or T-Bone, crashes.

What is the community concerned about?

During outreach events, local residents talked about aggressive driving behaviors that included driving at an unsafe speed and lack of attention paid to crossing pedestrians. Residents also described the difficulty crossing the street as a pedestrian because there are not enough marked crosswalks on the corridor.

The following pages lay out the existing conditions along the corridor, feedback heard from residents at outreach events, and a set of roadway safety recommendations focused on slowing drivers down and discouraging traffic signal/sign violations as well as providing more opportunities for pedestrians to cross the street at controlled, marked crossings.

Table of Contents



In the Neighborhood Travel on Marysville

B-6

B-8 B-11 B-10

Safety on Marysville Feedback from the Community **Investments to Enhance Safety**

Conceptual Design for Marysville



How Will Travel Change?

B-24

How Much Will the Project Cost?

In the Neighborhood

Corridor



About the Neighborhood



Residents of this neighborhood are more likely to take transit, but less likely to walk to work, when compared with the rest of the city.



Nearly 40% of the residents in this neighborhood are age 19 or under.



57% of the residents in this neighborhood are Black or Latino, compared with 42% citywide.







Key Destinations Along the Corridor

Parks



Houses of Worship



Schools



Community Centers



Food Markets



Travel on Marysville

Key Statistics




Crashes on Marysville

Vehicle Crash Types





Ped Crash Types Bike Crash Types



 Numbers that are turned on represent a location where crash type has occurred at least three times.



Feedback from the Community

Slow down traffic, drivers go over 35 MPH."

More signals and more crosswalks would make Marysville safer."



Key Themes

Visibility

Residents described visibility issues due to skew of intersections and presence of sight obstructions.

Signals/Signage

Residents suggested that more signals or flashing beacons could make it safer for pedestrians to cross the street.

Crossings

Residents described difficulty in crossing the street as a pedestrian because crosswalks are located far apart, and drivers do not pay attention to their presence.





Engagement Events

October 27, 2018

Mutual Assistance Harvest Festival, Robertson Community Center December 5, 2018

Hagginwood Community Association Meeting June 6, 2019

Greater Sacramento Urban League Open House Event

Investments to Enhance Safety

Key Crash Countermeasures



Conceptual Design for Marysville



Marysville Boulevard/Arcade Boulevard Queues

During peak hours, drivers use Marysville Boulevard and Arcade Boulevard between I-80 and the Arden-Arcade neighborhood. Therefore, there is a large southbound left-turn volume (595-vehicles) during the AM peak hour, and a large westbound right-turn volume (575-vehicles) during the PM peak hour. The southbound left-turn queue currently spills out of the available storage length of the turn pocket during peak hours, and this condition could be exacerbated by the recommended road diet. However, the recommendations also include the extension of the southbound left-turn lane to 750-feet, which would include restricting the Marysville Boulevard Boulevard/Ermina Drive intersection to right-in/right-out access only. The resulting maximum peak hour queues are shown in Appendix B.



Corridor-Wide Recommendations

Location-Specific Recommendations



Conceptual Design for Marysville



Vision Zero Top 5 Corridor



Corridor-Wide Recommendations

Location-Specific Recommendations



Conceptual Design for Marysville





Corridor-Wide Recommendations

Location-Specific Recommendations



Conceptual Design for Marysville



Vision Zero Top 5 Corridor



Corridor-Wide Recommendations

Location-Specific Recommendations



Conceptual Design for Marysville

Marysville Boulevard/North Avenue Queues

The Marysville Boulevard/North Avenue intersection is 475 feet away from the merge point of the I-80 eastbound off-ramp to the north. Measures should be taken to ensure that the southbound queue at the intersection does not spill back to the off-ramp. The conceptual plans show the southbound approach is comprised of two-through lanes with a lane drop as the road continues south. The peak hour maximum queues result from this configuration are in Appendix B.





Corridor-Wide Recommendations

Location-Specific Recommendations





How Will Travel Change?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 3 and 6 mph as a result of the proposed project.While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to increase between 52 and 110 seconds as a result of the proposed project.

Estimated Changes with Project



*Longest distance between crosswalks reduced from 1,230 to 800 ft.

*Longest distance between a bus stop and the closest crosswalk reduced from 630 to 230 ft.

How Much Will the Project Cost?

Marysville Boulevard Cost Summary

\$12,850,000

Construction

Construction costs include the cost to build the primary items associated with the safety countermeasures for the corridor. The items were estimated based on the preliminary design concepts and recent construction bid unit costs with an escalation factor to account for future construction. The costs were broken down into two categories that consisted of major roadway items and electrical items such as traffic signals and lighting. A contingency factor was included to account for refinement of project design, changes in project details, or unforeseen changes in construction costs.

Actual project costs will be determined by surveyed base mapping, geotechnical reports, concept refinement, environmental reviews, right of way availability, project phasing, and bid conditions at the time of advertisement. Project costs should be reviewed prior to any grant application or initiation of a Capital Improvement Project to revalidate and update the assumptions in this study as necessary.



The total project costs shown in the summary chart have been escalated at an assumed 3% per year escalation factor to 2025, the anticipated year of construction.

Right of Way

In addition to construction costs, right of way costs were assumed that include temporary construction easements for items such driveway modifications, curb ramps reconstruction, signal equipment poles and cabinets. The preliminary design assumes that the project can be constructed almost exclusively within the roadway prism and right of way acquisition along entire project frontage is not needed. Further refinement of the base mapping in subsequent phases of design will more accurately identify specific right of way needs.

Delivery

Project delivery costs are included in the estimates provided in this study. These costs encompass all of the work to complete subsequent phases including preliminary engineering, environmental documentation, final design, right of way engineering, and construction oversight. A breakdown of these costs is provided in Appendix C.



Broadway/Stockton

Vision Zero Top 5 Corridor

Broadway/Stockton Boulevard



Broadway/Stockton Blvd - Colonial Theater

What is going on?

Between 2009 and 2017, 15 crashes that resulted in a fatality or severe injury (KSI) occurred on Broadway/Stockton Boulevard between Martin Luther King Jr. Boulevard and 14th Avenue. Six of these crashes involved a pedestrian and three of these crashes involved a bicyclist. Of the 122 crashes studied on this corridor, 34 crashes (27 percent) occurred at the Broadway/Stockton Boulevard intersection.

What are the key issues?

Unsafe speed was the most common violation for vehicular crashes, and many drivers were proceeding straight or stopped at the time of the crash. On Broadway, half of the pedestrian crashes involved a pedestrian crossing the street outside of a crosswalk, whereas on Stockton Boulevard, 60 percent of pedestrians hit by drivers were crossing the street in a marked crosswalk. Bike crashes on this corridor involved broadside, or T-Bone, and sideswipe crashes.

What is the community concerned about?

Residents described frequent jaywalking activity throughout the corridor and suggested that it is result of lack of crosswalks, specifically near bus stops. Residents said it is uncomfortable to bike since there are gaps in the bike lanes and drivers tend to speed while traveling. The segment of Stockton Boulevard overlaps with the Stockton Boulevard Corridor Study.

The following pages lay out the existing conditions along the corridor, feedback heard from residents at outreach events, and a set of roadway safety recommendations focused on slowing drivers down, providing separated space for bicyclists, and giving pedestrians more opportunities for safe crossings.

C-2

Table of Contents

C-4

In the Neighborhood

Travel on Broadwav **C-8**

Travel on Stockton

C-10

Safety on **Broadway** **C-12**

C-6

Safety on Stockton

C-14

Feedback from the Community

C-15

Investments to Enhance Safety **C-18**

Conceptual Design for Broadway

C-24

Conceptual Design for Stockton

How Will Travel Change on Broadway

How Will Travel **Change on Stockton**

C-30 C-32 C-34

How Much Will the **Project Cost?**

In the Neighborhood

Corridors



About the Neighborhood



Residents take transit, walk, or bike to work at a higher rate than the city as a whole.



A larger share of residents in this neighborhood are age 20-69, compared with the city as a whole.



52% of the residents in this neighborhood are Black or Latino, compared with 42% citywide.



Key Destinations Along the Corridors



Travel on Broadway

Key Statistics





Travel on Stockton

Key Statistics





Crashes on Broadway

Vehicle Crash Types



Crash Locations



Pedestrian Crash Types



Numbers that are turned on represent a location where crash type has occurred at least three times.



Bike Crash Types



Crashes on Stockton

Vehicle Crash Types



Crash Locations



Ped Crash Types Bike Crash Types



 Numbers that are turned on represent a location where crash type has occurred at least three times.





Feedback from the Community

People drive too fast and run the right turn red lights at the Broadway/Stockton intersection."

"

More crosswalks! Cars do not stop, and there are bus stops not too far from crosswalks."



Key Themes

Pedestrian Safety

Residents said that this corridor has a lot of pedestrian activity but believed that drivers should travel more cautiously, specifically when making right-turns on the corridor or driving near crosswalks.

Speed

Residents described drivers speeding and traveling aggressively through the corridor and said they were uncomfortable walking and biking as a result.

Signals/Signage

Bike Safety

Residents described red light running at traffic signals and suggested that more traffic signals could slow down traffic.

to bike along the corridor since

the bike lanes are inconsistent.

Crossings

Residents described jaywalking throughout the corridor and suggested that it is result of lack of crosswalks specifically near bus stops.



Engagement Events

October 25, 2018

Fall Family Festival, Oak Park **Community Center**

November 7, 2018

Transit Stop at Broadway/ Stockton Pop-up

May 31, 2018 Let's Move! Event, McClatchy Park

Vision Zero Top 5 Corridor

Investments to Enhance Safety

Key Crash Countermeasures for Broadway



How Will The Roadway Space Be Used?





Investments to Enhance Safety

Key Crash Countermeasures for Stockton



How Will The Roadway Space Be Used?







Conceptual Design for Broadway




Location-Specific Recommendations



Conceptual Design for Broadway





Location-Specific Recommendations



Conceptual Design for Broadway





Location-Specific Recommendations



The Vision Zero recommendations include installation of traffic signals at Broadway/San Diego Way and Stockton Boulevard/6th Avenue. This would give pedestrians more opportunities to cross Broadway and Stockton Boulevard at desirable locations. However, City standard for minimum intersection spacing is 250-feet. The traffic signals at Broadway/San Diego Way and Stockton/6th Avenue would be 225-feet from the Broadway/Stockton Boulevard intersection, so the City would need to make exceptions to its Street Design Standards for this location. Traffic signals at these locations add more opportunities for controlled pedestrian crossings for popular pedestrian desire lines.

Conceptual Design for Stockton



Specific use of shaded area to be determined as part of on-going Stockton Boulevard Corridor Study.



Location-Specific Recommendations



Broadway/Stockton

Conceptual Design for Stockton







Conceptual Design for Stockton





Location-Specific Recommendations



- BROADWAY

How Will Travel Change on Broadway?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 1 and 5 mph as a result of the proposed project. While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to change ranging from a 6 second decrease to a 60 second increase seconds as a result of the proposed project.

Estimated Changes with Project





*Longest pedestrian crossing width reduced from 49 to 31 ft.

How Will Travel Change on Stockton?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 0 and 4 mph as a result of the proposed project. While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to increase up to 72 seconds as a result of the proposed project.

Estimated Changes with Project



*Longest pedestrian crossing distance reduced from 780 to 200 ft.

How Much Will the Project Cost?

Broadway/Stockton Boulevard Cost Summary

\$8,760,000

Construction

Construction costs include the cost to build the primary items associated with the safety countermeasures for the corridor. The items were estimated based on the preliminary design concepts and recent construction bid unit costs with an escalation factor to account for future construction. The costs were broken down into two categories that consisted of major roadway items and electrical items such as traffic signals and lighting. A contingency factor was included to account for refinement of project design, changes in project details, or unforeseen changes in construction costs.

Actual project costs will be determined by surveyed base mapping, geotechnical reports, concept refinement, environmental reviews, right of way availability, project phasing, and bid conditions at the time of advertisement. Project costs should be reviewed prior to any grant application or initiation of a Capital Improvement Project to revalidate and update the assumptions in this study as necessary.



The total project costs shown in the summary chart have been escalated at an assumed 3% per year escalation factor to 2025, the anticipated year of construction.

Right of Way

In addition to construction costs, right of way costs were assumed that include temporary construction easements for items such driveway modifications, curb ramps reconstruction, signal equipment poles and cabinets. It was assumed that each project could be constructed almost exclusively within the roadway prism and right of way acquisition would not be needed along the entire project frontage. Further refinement of the base mapping in subsequent phases of design will more accurately identify specific right of way needs.

Delivery

Project delivery costs are included in the estimates provided in this study. These costs encompass all of the work to complete subsequent phases including preliminary engineering, environmental documentation, final design, right of way engineering, and construction oversight. A breakdown of these costs is provided in Appendix C.



Stockton (South)

Vision Zero Top 5 Corridor

Stockton Boulevard (South)

Vision Zero Top 5 Corridor



South Stockton Blvd - Vinh Phat Supermarket

What is going on?

Between 2009 and 2017, 16 crashes that resulted in a fatality or severe injury (KSI) occurred on Stockton Boulevard between McMahon Drive and Patterson Way. Nine of these crashes involved a person walking or biking.

What are the key issues?

Unsafe speed was the most commonly cited violation, while nearly three-fourths of driving were proceeding straight or stopped at the time of the crash. Additionally, nearly half of all pedestrians hit by a driver were crossing in a marked crosswalk. One-third of drivers who hit a bicyclist were making a right-turn.

What is the community concerned about?

At outreach events, residents described aggressive driving behavior along the corridor that included driving at unsafe speeds and traffic signal violations. Many residents also said they avoid biking on this segment of Stockton Boulevard because of gaps in the bike lane. The following pages lay out the existing conditions along the corridor, feedback heard from residents at outreach events, and a set of roadway safety recommendations focused on slowing drivers down, improving compliance with signals and signs, and improving safety for people walking and biking.

Table of Contents



In the Neighborhood Travel on Stockton (South)

D-6

D-8 D-10

D-11

Safety on Stockton (South) Feedback from the Community **Investments to Enhance Safety**

Conceptual Design for Stockton (South)



How Will Travel Change?

How Much Will the Project Cost?

In the Neighborhood

Corridor



About the Neighborhood









Key Destinations Along the Corridor

Schools







Houses of Worship



Travel on Stockton (South)

Key Statistics





Crashes on Stockton (South)

Vehicle Crash Types



Crash Locations



Ped Crash Types Bike Crash Types



Numbers that are turned on represent a location where crash type has occurred at least three times.



Stockton (South)

Feedback from the Community

"

I won't ride my bike along this corridor because it feels unsafe."

My grandma picks me up from school and there are a lot of fast cars."



Key Themes

Bike/Pedestrian Safety

Residents described avoiding biking on Stockton Boulevard because it feels unsafe and there is a lack of connectivity to other bike facilities.

Speed

Residents described traffic speeding along the corridor.



Signals/Signage

Residents described red light running, particularly at the Stockton Boulevard/McMahon Drive intersection.

Engagement Events

November 5, 2018

Peter Burnett Elementary School Community Workshop June 5, 2019

Luther Burbank High School Community Open House

Investments to Enhance Safety

Key Crash Countermeasures



How Will The Roadway Space Be Used?

Section D **Existing**

Stockton (South)





Conceptual Design for Stockton (South)





Location-Specific Recommendations



Conceptual Design for Stockton (South)





Location-Specific Recommendations





Conceptual Design for Stockton (South)





Vision Zero Top 5 Corridor



Location-Specific Recommendations



Conceptual Design for Stockton (South)









Conceptual Design for Stockton (South)




Location-Specific Recommendations





Stockton (South)

How Will Travel Change?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 1 and 3 mph as a result of the proposed project. While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to increase between 6 and 48 seconds as a result of the proposed project.

Estimated Changes with Project





How Much Will the Project Cost?

Stockton Boulevard (South) Cost Summary

\$9,500,000

Construction

Construction costs include the cost to build the primary items associated with the safety countermeasures for the corridor. The items were estimated based on the preliminary design concepts and recent construction bid unit costs with an escalation factor to account for future construction. The costs were broken down into two categories that consisted of major roadway items and electrical items such as traffic signals and lighting. A contingency factor was included to account for refinement of project design, changes in project details, or unforeseen changes in construction costs.

Actual project costs will be determined by surveyed base mapping, geotechnical reports, concept refinement, environmental reviews, right of way availability, project phasing, and bid conditions at the time of advertisement. Project costs should be reviewed prior to any grant application or initiation of a Capital Improvement Project to revalidate and update the assumptions in this study as necessary.



The total project costs shown in the summary chart have been escalated at an assumed 3% per year escalation factor to 2025, the anticipated year of construction.

Right of Way

In addition to construction costs, right of way costs were assumed that include temporary construction easements for items such driveway modifications, curb ramps reconstruction, signal equipment poles and cabinets. It was assumed that each project could be constructed almost exclusively within the roadway prism and right of way acquisition would not be needed along the entire project frontage. Further refinement of the base mapping in subsequent phases of design will more accurately identify specific right of way needs.

Delivery

Project delivery costs are included in the estimates provided in this study. These costs encompass all of the work to complete subsequent phases including preliminary engineering, environmental documentation, final design, right of way engineering, and construction oversight. A breakdown of these costs is provided in Appendix C.



Florin Road

Vision Zero Top 5 Corridor



What is going on?

Between 2009 and 2017, 16 crashes that resulted in a fatality or severe injury (KSI) occurred on Florin Road between 24th Street and Munson Way. Eight of these crashes involved a person walking or biking.

00

What are the key issues?

Three-fourths of drivers who crashed were proceeding straight or stopped at the time of the crash, and nearly half of all crashes cited unsafe speed as the primary violation. Of the pedestrians who were hit, half were crossing the street in a marked crosswalk at the time. Nearly 40 percent of bike crashes involved a driver making a right-turn.

What is the community concerned about?

At outreach events, residents described difficulty crossing the street, particularly near the Florin Light Rail Station and Luther Burbank high school.

The following pages lay out the existing conditions along the corridor, feedback heard from residents at outreach events, and a set of roadway safety recommendations focused on slowing down drivers, increasing compliance with signals and signs, and improving safety for people walking and biking

Table of Contents



In the Neighborhood Travel on Florin

E-6

E-8 E-10

Safety on Florin

Feedback from the Community

E-11 Investments to Enhance Safety

Conceptual Design for Florin



How Will Travel Change?

How Much Will the Project Cost?

In the Neighborhood

Corridor



About the Neighborhood



A larger share of residents in this neighborhood walk to work, when compared to the city as a whole.



36% of residents in this neighborhood are age 19 or younger, compared with 26% of residents citywide.



81% of residents in this neighborhood identify as Latino, Black or Asian, compared with 61% of residents citywide.







Key Destinations Along the Corridor

Parks



Houses of Worship



Schools & Libraries



Light Rail Stations

Food Markets



Travel on Florin

Key Statistics





Crashes on Florin

Vehicle Crash Types



Crash Locations



Vision Zero Top 5 Corridor

Ped Crash Types Bike Crash Types



Numbers that are turned on represent a location where crash type has occurred at least three times.



Feedback from the Community

We need to slow drivers down."

The signals need more time for crossing (when seniors cross it is too short)."



Key Themes

Traffic Enforcement

Residents described speeding, and red light and stop sign running across the corridor and suggested increased speed enforcement could deter this behavior.

Other 24% Crossings 32%

Crossings

Residents described difficulty crossing the street, particularly by the Florin light rail station and Luther Burbank High School, due to large spacing between marked crosswalks.

Engagement Events

November 15, 2018

Luther Burbank High School Community Workshop May 5, 2019

Luther Burbank High School Community Open House

Investments to Enhance Safety

Key Crash Countermeasures



How Will The Roadway Space Be Used?

Section E
Existing





Conceptual Design for Florin







Location-Specific Recommendations





Conceptual Design for Florin







Location-Specific Recommendations



Conceptual Design for Florin









Location-Specific Recommendations





Conceptual Design for Florin







Florin Road/Serenity Drive Queues

The Florin Road/Serenity Drive intersection is approximately 450feet east of railroad tracks operated by Union Pacific Railroad. If a signal is installed at Florin Road/Serenity Drive, measures should be taken to ensure the eastbound queue does not spill back onto the railroad.

Queues were calculated from SimTraffic models representing existing conditions with the Vision Zero recommendations implemented. The peak hour maximum queues of this new signal are shown in Appendix B.



Location-Specific Recommendations



Conceptual Design for Florin









Location-Specific Recommendations



Consolidate

Driveways

Pedestrian

Refuge Island

New Traffic

Signal

How Will Travel Change?

Estimated Changes with Project

Average Vehicle Speed

Average vehicle speed along the corridor during peak periods is expected to decrease between 1 and 3 mph as a result of the proposed project. While slower travel speeds result in longer travel times, they reduce traffic fatalities and severe injuries that result from crashes.





Vehicle Travel Time

Average vehicle travel time along the one-mile corridor during peak periods is expected to increase between 13 and 36 seconds as a result of the proposed project.

Estimated Changes with Project







Number of Locations Upgraded to Controlled Crossings

3

Number of Marked Crosswalks



How Much Will the Project Cost?

Florin Road Cost Summary

\$11,900,000

Construction

Construction costs include the cost to build the primary items associated with the safety countermeasures for the corridor. The items were estimated based on the preliminary design concepts and recent construction bid unit costs with an escalation factor to account for future construction. The costs were broken down into two categories that consisted of major roadway items and electrical items such as traffic signals and lighting. A contingency factor was included to account for refinement of project design, changes in project details, or unforeseen changes in construction costs.

Actual project costs will be determined by surveyed base mapping, geotechnical reports, concept refinement, environmental reviews, right of way availability, project phasing, and bid conditions at the time of advertisement. Project costs should be reviewed prior to any grant application or initiation of a Capital Improvement Project to revalidate and update the assumptions in this study as necessary.



The total project costs shown in the summary chart have been escalated at an assumed 3% per year escalation factor to 2025, the anticipated year of construction.

Right of Way

In addition to construction costs, right of way costs were assumed that include temporary construction easements for items such driveway modifications, curb ramps reconstruction, signal equipment poles and cabinets. It was assumed that each project could be constructed almost exclusively within the roadway prism and right of way acquisition would not be needed along the entire project frontage. Further refinement of the base mapping in subsequent phases of design will more accurately identify specific right of way needs.

Delivery

Project delivery costs are included in the estimates provided in this study. These costs encompass all of the work to complete subsequent phases including preliminary engineering, environmental documentation, final design, right of way engineering, and construction oversight. A breakdown of these costs is provided in Appendix C.



TOP 5 CORRIDORS



Appendix A Related Documents

Cechnical Calculations

Concept Plans & Cost Estimates Abbendix Abbendix
Vision Zero Top 5 Corridors FAQS



The Vision Zero Top 5 Corridors study represents a next step of the Sacramento Vision Zero Action Plan, focusing efforts on implementing near-term roadway improvements on the five corridors in the city that have the highest rate of crashes that result in fatalities and severe injuries. During public outreach and public comment of this study, a few common questions were posed that were not covered in the Vision Zero Top 5 Corridors report. Responses to those questions are provided below.

1. Why aren't new trees and landscaping included in the Plan?

The recommendations in the Vision Zero Top 5 Corridors Plan are focused on roadway design features that will improve safety based on the collision data that was analyzed. The project team did not identify locations in which a landscape buffer addressed collisions and was a feasible option. There are some recommendations that will require changes to the existing landscaping, such as the modified sidewalk on Florin Rd. and the realignment of the intersection of El Camino Rd. and the Sacramento Northern Bike Trail. This plan does not preclude new trees, landscaping, and other placemaking elements from being considered in the future where there is available space and financial resources to maintain.

${f 2.}$ Why does the plan propose so many new traffic signals?

New traffic signals organize interactions between vehicles, pedestrians, and bicyclists with conflicting movements, and provide an improved crossing for pedestrians. New traffic signals can also slow traffic on long, high-speed straightaways when timed properly. Consistently spaced traffic signals facilitate the "slow green wave" in which signals are coordinated for slower travel speeds.

3. Can you set lower speed limits to reduce speed?

Cities in the State of California must adhere to the California Vehicle Code for setting speed limits. The process for setting speed limits on non-residential streets includes conducting a specific speed survey to determine the, "prevailing speed." The prevailing speed is the speed which 85 percent of the motorists are traveling at or below. The speed limit is set using the prevailing speed, with considerations for other factors such as the type of adjacent development, bicycle and pedestrian activity, and reported collision history. This process prohibits cities from arbitrarily setting speed limits. Roadway design can help to influence prevailing speeds, meaning that in the future a lower speed limit may be warranted along corridors where roadway safety improvements have been made.

4. Will my street be considered for safety improvements?

Per the City of Sacramento's Vision Zero Action Plan, safety improvements are prioritized where historic collision data points to the most need. These locations together are called the High Injury Network. The City's transportation funding priorities include an emphasis on funding future safety projects on the High Injury Network.